

Description: 16AWG Multicore LSHF speaker cables. Oxygen free copper conductors, features a quick strip jacket for easy installation

truSOUND



Construction

Conductor Material : 99.999% Oxygen Free Bare Copper
 Number of Strands : 41/0.2mm
 Insulation Material : Low Smoke Halogen Free (LSHF)
 Sheath Material : Low Smoke Halogen Free (LSHF)
 Sheath Colour : See Table
 Core Identification : 2 Core – Red & Black
 : 4 Core – Red, Black, Green & White

Electrical Characteristics

Nominal Conductor Resistance : < 13.7 Ω/km
 Insulation Resistance : > 200 MΩ.M
 Voltage Rating : 450/750V
 Test Voltage : 2.5kV for 5 Minutes

Physical Characteristics

Overall Diameter : See table
 Min. Bend Radius : 10 x OD
 Temperature Rating : 0°C to +70°C
 Weight : See table

Standards

RoHS2 Complaint : Yes
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : E_{CA} (EN50575:2014+A1:2016)

Part No.	No. Cores	Outer Sheath Colour	Weight (kg/km)	OD (mm)
TSS162H-E00	2	Violet	35	6.1
TSS162HW-E00	2	White	35	6.1
TSS162H07-E00	2	Pink	35	6.1
TSS162H08-E00	2	Orange	35	6.1
TSS164H-E00	4	Violet	54	7.1
TSS164HW-E00	4	White	54	7.1
TSS164H07-E00	4	Pink	54	7.1
TSS164H08-E00	4	Orange	54	7.1

Tru Cables Tel: 01727 840 841 info@trucables.com www.trucables.com

Information and images on this datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.

ISO 9001:2015 Certificate Number: DAS94272226/0/Q

Date: 07/07/2017
 Revision: 1.0
 Author: TB Checked:
 Page Number: 1 of 1